

## **STRUGARKA CZTEROSTRONNA AUTOMATYCZNA - 3PI6011.M205UM089**

Model: RMM623U

SCORNICIATRICE AUTOMATICA A 5+1 ALBERI MOD. RMM623U - CE

5+1 SPINDLES MOULDER RMM623U

Working width (cutter OD110mm) 20-230

Working thickness (cutter OD110mm) 8-160

spindle QTY 5+1

- Dia of shaft (mm) Ø40

spindle rotation speed(r/min) 1st bottom spindle 6000

right spindle 6000

left spindle 6000

top spindle 6000

2nd bottom spindle 6000

Universal spindle 6000

Cutting circle

(mm) 1st bottom spindle Ø110 ~ Ø145

right spindle Ø110 ~ Ø200

left spindle Ø110 ~ Ø200

top spindle Ø110 ~ Ø200

2nd bottom spindle Ø110 ~ Ø200

Universal spindle Ø110 ~ Ø180

max OD of saw blade on universal spindle□mm□ Ø350

max cutter length on universal spindle□mm□ 240

rotation angle of universal spindle 360°

(kW)

Motor power

1st bottom spindle 5.5 kW/7.5HP

right spindle 5.5 kW/7.5HP

left spindle 7.5 kW/10HP

top spindle 7.5 kW/10HP

2nd bottom spindle 7.5 kW/10HP

universal spindle 7.5 kW/10HP

universal spindle lift 0.18 kW/0.25HP

feed 5.5kW/7.5HP

feed beam lift 0.75kW/1HP

Total motor power(KW) 45.43kW/61.25HP

Feeding speed(m/min)

(inverter to feed) 6~30



Caselli Group SPA  
Via Nazionale, 87  
33048 - San Giovanni al Natisone  
Udine - Italia  
Tel: +39 0432 757 064  
Web: [www.casellispa.com](http://www.casellispa.com)  
Email: [info@casellispa.com](mailto:info@casellispa.com)

top pressure roller dia ,OD/ID (mm) Ø140/ Ø35

dust suction pipe Dia. (mm) Ø150