

FERASTRAU PANGLICA ORIZZONTAL PENTRU LAMELAT - 4SS222502

Model: TS400

SECOND HAND TS 400 THIN CUTTING HORIZONTAL BANDSAW CE rules

SECOND-HAND TS 400 THIN CUTTING HORIZONTAL BANDSAW CE rules

TECHNICAL DATA:

SPECIAL DEVICE "OFFSET":

DEVICE "DOUBLE SPEED":

Max. cutting capacity 420x200 mm

Distance from blade to conveyor 2-150mm

Min. cutting thickness from the top 0.75 mm

Saw wheel diam. 800 mm.

Saw wheel thickness 50 mm

Sawblade length 5500 mm.

Sawblade width 50 mm.

Sawblade speed 17-34 m/s

Conveyor belt size 400x4200mm

Oil mist cooling system

High accuracy hydraulic blade tension system (2500 kg)

Variable feed speed 0-25 m/min

Feed motor 2HP with inverter

Main motor 30 HP with inverter

Blade lift motor 2 HP

Dust hood outlet diam. 125 mm x 2

Machine net weight Kg. 3100

Air loaded pressure roller

Slow cutting start function

spraying jets for blade lubrication

motor IE3 INCLUDED

- SN 15084

- YEAR 2022





Caselli Group SPA
Via Nazionale, 87
33048 - San Giovanni al Natisone
Udine - Italia
Tel: +39 0432 757 064
Web: www.casellispa.com
Email: info@casellispa.com
