Caselli Group SPA
Via Nazionale, 87
33048 - San Giovanni al Natisone
Udine - Italia
Tel: +39 0432 757 064
Web: www.casellispa.com
Email: info@casellispa.com

ГОРИЗОНТАЛЬНЫЙ ЛЕНТОЧНОПИЛЬНЫЙ СТАНОК ДЛЯ ЛАМЕЛЕЙ - 4SS222502

Model: TS400

SECOND HAND TS 400 THIN CUTTING HORIZONTAL BANDSAW CE rules

SECOND-HAND TS 400 THIN CUTTING HORIZONTAL BANDSAW CE rules
TECHNICAL DATA:
SPECIAL DEVICE "OFFSET":
DEVICE "DOUBLE SPEED":
Max. cutting capacity 420x200 mm
Distance from blade to conveyor 2-150mm
Min. cutting thickness from the top 0.75 mm
Saw wheel diam. 800 mm.
Saw wheel thickness 50 mm
Sawblade length 5500 mm.
Sawblade width 50 mm.
Sawblade speed 17-34 m/s
Conveyor belt size 400x4200mm
Oil mist cooling system
High accuracy hydraulic blade tension system (2500 kg)
Variable feed speed 0-25 m/min
Feed motor 2HP with inverter
Main motor 30 HP with inverter
Blade lift motor 2 HP
Dust hood outlet diam. 125 mm x 2
Machine net weight Kg. 3100
Air loaded pressure roller
Slow cutting start function
spraying jets for blade lubrication
motor IE3 INCLUDED
- SN 15084
- YEAR 2022

Caselli Group SPA
Via Nazionale, 87
33048 - San Giovanni al Natisone
Udine - Italia
Tel: +39 0432 757 064
Web: www.casellispa.com
Email: info@casellispa.com





